









NSR-9512YDC

LED Polymer Rechargeable Single Button Flashlight w/3 Brightness Modes & Strobe

MARKET APPLICATIONS	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
DESCRIPTION	The NSR-9512 rechargeable glass-filled nylon polymer LED flashlight, offers 3 microprocessor-controlled brightness modes as well as a strobe function. Utilizing a CREE® LED, the 9512 has an impressive runtime of 4.5 hours in high-brightness mode. The 350 lumen output in combination with the high efficiency deep parabolic reflector design throws a usable beam of light 313 meters...that's over 1,026 feet. The 9512 has a single button design, located on the waterproof body of the light.
CASE MATERIAL	Yellow Glass-filled Nylon Polymer w/ Aircraft-grade 6061-T6 Aluminum Tail Cap and a 316 Stainless Steel bezel both with a Type 3 Hard Anodized Finish.
DIMENSIONS	Length: 8.9 inches (226 mm) • Handle diameter 1.2 inches (30 mm) • Head diameter 1.6 inches (41 mm)
WEIGHT	Weight: 10.1 oz. (286 g) with battery installed.
LENS	Unbreakable polycarbonate with scratch resistant coating.
LIGHT SOURCE	Cree® LED. Impervious to shock with a 50,000 + hour lifetime.
LIGHT OUTPUT	High - 350 lumens • Medium - 200 lumens • Low 55 lumens • Strobe - 300 lumens
ON/OFF	Single Body Switch - Momentary & Constant-on, High, Medium & Low-Brightness & Strobe.
RUN-TIME	High-brightness mode - 4.5 hours • Medium-brightness mode - 8.5 hours • Low-brightness mode - 32.5 hours • Strobe - 5.5 hours.
BATTERY	2-cell, 3.7 Volt Lithium-ion battery pack.
CHARGING	Charging platform is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.
FEATURES	<ul style="list-style-type: none"> • Microprocessor controlled single button design – body • Multiple lighting modes: momentary or constant-on flashlight, three brightness modes (high, medium & low) & strobe • CREE® LED has a 50,000 + hour life • Body is made from glass-filled nylon polymer • Tail cap is machined from aircraft-grade 6061-T6 aluminum and the bezel is machined from 316 stainless steel both with a Type 3 hard anodized finish - black • Unbreakable polycarbonate lens with scratch-resistant coating • Non-slip grip • IP-X7 rated waterproof • Drop rated to 2 meters • Rechargeable/replaceable lithium-ion battery • Serialized for personal identification • Includes wall or vehicle mounted charger as well as the DC power supply and anti-roll ring
WARRANTY	Limited Lifetime warranty • Lifetime on LED, housing, lens, electronics and switches. One year on battery pack and chargers from date of purchase. Excludes normal wear and abuse.
APPROVALS	 This product's components are in compliance with the European Union's directive 2002/95/EC, Restrictions of Hazardous Substances (RoHS)
OPTIONAL ACCESSORIES	AC power supply, 5 bank charger, Spare Lithium-ion battery pack, USB Cord, Red, Yellow or Blue safety cones, and a leather holster

FL 1 STANDARD	 High / Mid / Low 350 / 200 / 55 LUMENS	 2m	 High 313m Mid 235m Low 118m
	 High 4.25h Mid 8.5h Low 32.5h	 1m	 High 24100cd Mid 12075cd Low 6200cd



Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

PDS_NSR-9512YDC_130418_A