

## NSR-9612B

## LED Metal Rechargeable Single Button Flashlight w/3 Brightness Modes & Strobe

MARKET APPLICATIONS Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.

**DESCRIPTION**The NSR-9612 rechargeable aircraft-grade aluminum LED flashlight, offers 3 microprocessor-controlled brightness

modes as well as a strobe function. Utilizing a CREE® LED, the 9612 has an impressive runtime of 4.5 hours in high-brightness mode. The 220 lumen output in combination with the high efficiency deep parabolic reflector design throws a usable beam of light 345 meters...that's over 1,130 feet. The 9612 has a single button design, located on the

waterproof body of the light.

**CASE MATERIAL** Aircraft-grade 6061-T6 Aluminum with Type 3 Hard Anodized Finish.

**DIMENSIONS** Length: 8.9 inches (226 mm) • Handle diameter 1.2 inches (30 mm) • Head diameter 1.6 inches (41 mm)

**WEIGHT** Weight: 12.8 oz. (363 g) with battery installed.

LIGHT SOURCE

Unbreakable polycarbonate with scratch resistant coating.

Cree® LED. Impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT High - 220 lumens • Medium - 120 lumens • Low 40 lumens • Strobe - 200 lumens

**0N/0FF** Single Body Switch - Momentary & Constant-on, High, Medium & Low-Brightness & Strobe.

RUN-TIME High-brightness mode - 4.5 hours • Medium-brightness mode - 9 hours • Low-brightness mode - 33 hours • Strobe - 6

hours.

**BATTERY** 2-cell, 3.7 Volt Lithium-ion battery pack.

Charging platform is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.

• Microprocessor controlled single button design – body

• Multiple lighting modes:momentary & constant-on flashlight, three brightness modes (high, medium & low) & strobe

• CREE® LED has a 50,000 hour life

• Body is machined from aircraft-grade 6061-T6 aluminum

• Type 3 hard anodized finish - black

· Unbreakable polycarbonate lens with scratch-resistant coating

· Non-slip grip

WARRANTY

IP-X7 rated waterproofDrop rated to 2 meters

• Diopiated to 2 meters

Rechargeable/replaceable lithium-ion battery

• Serialized for personal identification

• Includes wall or vehicle mounted charger as well as AC and DC power supply

Limited Lifetime warranty • Lifetime on LED, housing, lens, electronics and switches. One year on battery pack and


chargers from date of purchase. Excludes normal wear and abuse.


This product's components are in compliance with the European Union's directive 2002/95/EC, Restrictions of Hazardous Substances (RoHS)

**OPTIONAL ACCESSORIES** 5 bank charger, Spare Lithium-ion battery pack, USB Cord - 27 inches, Red, Yellow or Blue safety cones, and a leather

holster

9612/14 LED PERFORMANCE CURVE





PDS\_NSR-9612B\_120730\_A