

4:30

4:15

PDS_NSR-9614B_120730_A

NSR-9614B

LED Metal Rechargeable Dual Button Flashlight w/3 Brightness Modes & Strobe

MARKET APPLICATIONS	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
DESCRIPTION	The NSR-9614 rechargeable aircraft-grade aluminum LED flashlight, offers 3 microprocessor-controlled brightness modes as well as a strobe function. Utilizing a CREE [®] LED, the 9614 has an impressive runtime of 4.5 hours in high-brightness mode. The 220 lumen output in combination with the high efficiency deep parabolic reflector design throws a usable beam of light 345 metersthat's over 1,130 feet. The 9614 has a dual button design, one located on the waterproof body of the light, and the other in the tail cap. Both buttons operate in tandem with each other.
CASE MATERIAL	Aircraft-grade 6061-T6 Aluminum with Type 3 Hard Anodized Finish.
DIMENSIONS	Length: 8.9 inches (226 mm) • Handle diameter 1.2 inches (30 mm) • Head diameter 1.6 inches (41 mm)
WEIGHT	Weight: 12.8 oz. (363 g) with battery installed.
LENS	Unbreakable polycarbonate with scratch resistant coating.
LIGHT SOURCE	Cree [®] LED. Impervious to shock with a 50,000 hour lifetime.
LIGHT OUTPUT	High - 220 lumens • Medium - 120 lumens • Low 40 lumens • Strobe - 200 lumens
ON/OFF	Single Body Switch & Single Tail Switch (Tandom Functionality) - Momentary & Constant-on, High, Medium & Low- Brightness & Strobe.
RUN-TIME	High-brightness mode - 4.5 hours • Medium-brightness mode - 9 hours • Low-brightness mode - 33 hours • Strobe - 6 hours.
BATTERY	2-cell, 3.7 Volt Lithium-ion battery pack.
CHARGING	Charging platform is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.
FEATURES	 Microprocessor controlled dual button design – body & tail cap Multiple lighting modes:momentary & constant-on flashlight, three brightness modes (high, medium & low) & strobe CREE® LED has a 50,000 hour life Body is machined from aircraft-grade 6061-T6 aluminum Type 3 hard anodized finish - black Unbreakable polycarbonate lens with scratch-resistant coating Non-slip grip IP-X7 rated waterproof Drop rated to 2 meters Rechargeable/replaceable lithium-ion battery Serialized for personal identification Includes wall or vehicle mounted charger as well as AC and DC power supply
WARRANTY	Limited Lifetime warranty • Lifetime on LED, housing, lens, electronics and switches. One year on battery pack and chargers from date of purchase. Excludes normal wear and abuse.
APPROVALS	Meets European Community Directives ROHS Lagrandous Substances (RoHS) Meets European Union's directive 2002/95/EC, Restrictions of Hazardous Substances (RoHS)
OPTIONAL ACCESSORIES	5 bank charger, Spare Lithium-ion battery pack, USB Cord - 27 inches, Red, Yellow or Blue safety cones, and a leather
	9612/14 LED PERFORMANCE CURVE
	Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constraint of the system Image: Constre system Image: Constrele system Image:

Low 33.0h Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

Mid **9.0h**

Bayco • 640 S. Sanden Blvd • Wylie, TX 75098 • 800.233.2155 • www.baycoproducts.com

Mid **15630cd**

Low 5030cd

1m

UMENS.

HOURS