

XPP-5450G

Safety Rated/Intrinsically Safe Dual-Function LED Headlamp

Hazardous work environments, law enforcement, fire & rescue, industrial, automotive MARKET APPLICATIONS

DESCRIPTION This Safety Rated Intrinsically Safe Dual-Function LED Headlamp is designed for use in hazardous workplace

environments by professionals needing the ultimate in hands-free lighting. Ideal for head or hardhats, the XPP-5450G is cETLus Listed Intrinsically Safe for use in Class I, II, III, Div 1, Groups A, B, C, D, E, F & G hazardous locations. The XPP-5450G headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining for use on a head or hat and a heavy-duty rubber head strap for use on hardhats. The top mounted switch provides user-

selectable high or low-brightness spotlight operation.

CASE MATERIAL Engineered Polymer

Width: 2.4 inches (61 mm) • Height 1.9 inches (48 mm) • Depth 1.8 inches (46 mm) **DIMENSIONS**

WEIGHT Weight: 3.5 oz. (99 g) with batteries installed

LENS Unbreakable polycarbonate with scratch resistant coating

LIGHT SOURCE Spotlight: CREE® LED Impervious to shock with a 50,000 hour lifetime

High-brightness Spotlight - 60 lumens • Low-brightness Spotlight - 40 lumens **LIGHT OUTPUT**

ON/OFF Single Switch - High-brightness Spotlight • Low-brightness Spotlight

RUN-TIME High-brightness Spotlight - 13.5 hours • Low-brightness Spotlight - 22.75 hours

3 Premium alkaline AAA batteries (included) **BATTERY**

FEATURES · High-brightness spotlight, low-brightness spotlight

- CREE® LED technology 50,000 + hours LED life
- · Focused spotlight beam for distance illumination
- IP-X7 Waterproof
- Drop rated to 2 meters
- Impact & chemical resistant
- · Engineered polymer housing
- · Single switch located on top of light
- · Adjustable ratchet tilt head
- Includes Non-slip elastic head strap, Heavy-duty rubber strap for hard hat applications and 3 premium AAA alkaline batteries

WARRANTY

Limited Lifetime warranty · Lifetime on LEDs, housing, lens, electronics and switches. Batteries, normal wear and abuse are excluded.


APPROVALS




cETLus Listed Intrinsically Safe for use in Class I II III Div 1 SECRURITE INTRINSEQUE Groups A,B,C,D,E,F & G s Hazardous Locations -20C < Tamb <+40C • Ex ia IIC T3 Ga Class 1 Zone 0 • AEx ia IIC T3 Ga, Zone 20 • AEx ia IIIC T 165C Da



RoHS This product's components are in compliance with the European Union's directive 2002/95/EC, Restrictions of Hazardous Substances (RoHS)





PDS_XPP-5450G_130121_A