



## XPP-5452G

## Safety Rated/Intrinsically Safe Dual-Function LED Headlamp

MARKET APPLICATIONS	Hazardous work environments, law enforcement, fire & rescue, industrial, automotive
DESCRIPTION	This Safety Rated Intrinsically Safe Dual-Function LED Headlamp is designed for use in hazardous workplace environments by professionals needing the ultimate in hands-free lighting. Ideal for head or hardhats, the XPP-5452G is cETLus Listed Intrinsically Safe for use in Class I, II, III, Div 1, Groups A, B, C, D, E, F & G hazardous locations. The XPP-5452G headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining for use on a head or hat and a heavy-duty rubber head strap for use on hardhats. The top mounted switch provides user-selectable high or low-brightness spotlight operation.
CASE MATERIAL	Engineered Polymer
DIMENSIONS	Width: 2.4 inches (61 mm) • Height 1.9 inches (48 mm) • Depth 1.8 inches (46 mm)
WEIGHT	Weight: 3.5 oz. (99 g) with batteries installed
LENS	Unbreakable polycarbonate with scratch resistant coating
LIGHT SOURCE	Spotlight: CREE® LED Impervious to shock with a 50,000 hour lifetime
LIGHT OUTPUT	High-brightness Spotlight - 115 lumens • Low-brightness Spotlight - 65 lumens
ON/OFF	Single Switch - High-brightness Spotlight • Low-brightness Spotlight
RUN-TIME	High-brightness Spotlight - 4.5 hours • Low-brightness Spotlight - 13 hours
BATTERY	3 Premium alkaline AAA batteries (included)
FEATURES	<ul> <li>High-brightness spotlight, low-brightness spotlight</li> <li>CREE® LED technology - 50,000 + hours LED life</li> <li>Focused spotlight beam for distance illumination</li> <li>IP-X7 Waterproof</li> <li>Drop rated to 2 meters</li> <li>Impact &amp; chemical resistant</li> <li>Engineered polymer housing</li> <li>Single switch located on top of light</li> <li>Adjustable ratchet tilt head</li> <li>Includes Non-slip elastic head strap, Heavy-duty rubber strap for hard hat applications and 3 premium AAA alkaline batteries</li> </ul>
WARRANTY	Limited Lifetime warranty • Lifetime on LEDs, housing, lens, electronics and switches. Batteries, normal wear and abuse are excluded.
APPROVALS	cETLus Listed Intrinsically Safe for use in Class I II III Div 1 SECRURITE INTRINSEQUE Groups A,B,C,D,E,F & G Hazardous Locations -20C < Tamb <+40C • Ex ia IIC T3 Ga Class 1 Zone 0 • AEx ia IIC T3 Ga, Zone 20 • AEx ia IIIC T 165C Da
	Rous This product's components are in compliance with the European Union's directive 2002/95/EC, Restrictions of

This product's components are in compliance with the European Union's directive 2002/95/EC, Restrictions of Hazardous Substances (RoHS)





Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

PDS\_XPP-5452G\_130121\_A