

Intrinsically Safe Dual-Function licadiamp

NIGHT

(GHI

These non-rechargeable dual-function headlamps are cETLus listed Intrinsically Safe for use in Class I, II, III, Division I, Groups A-G hazardous workplace environments. The headlamps each feature a multi-position tilt head design and include an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The top mounted switch provides user selectable high or low brightness spotlight operation. Power comes from 3 AAA premium batteries (included).

XPP-5450G

NIGH

(IGH)

INTRINSICALLY SAFE



60 115

Spotlight Lumens

- Class I, II, III, Division I, Groups A-G
- High/low brightness spotlight
- 80/92 Meter beam distance
- Engineered polymer housing






XPP-5452G



TEP 54 50 series



High/Low-brightness

Spotlight





FEATURES

- CREE® LED technology 50,000 + hours LED life
- High-brightness spotlight, low-brightness spotlight
- Focused spotlight beam for distance illumination
- Engineered polymer housing
- Single switch located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Heavy-duty rubber strap for hard hat applications
- Waterproof
- Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)
- Limited Lifetime Warranty*

SAFETY RATING

cETLus Listed Intrinsically Safe for use in Class I II III Div 1 SECRURITE INTRINSEQUE Groups A, B, C, D, E, F & G Hazardous Locations -20C < Tamb <+40C • Ex ia IIC T3 Ga Class 1 Zone 0 • AEx ia IIC T3 Ga, Zone 20 • AEx ia IIIC T 165C Da

INCLUDED

- Headlamp
- 3 Premium alkaline AAA batteries
- Elastic non-slip head strap
- Heavy-duty rubber hard hat strap




XPP-5450G SPECIFICATIONS

- Lumens: high spotlight-60, low spotlight-40


XPP-5450G

- Run-time: high spotlight-13.5 hrs, low spotlight-22.75 hrs
- Beam distance: 80 meters
- Water rating: IP-X7
- Drop rating: 2 meters
- Width: 2.4in, height: 1.9in, depth: 1.8in, weight: 3.5oz



XPP-5452G SPECIFICATIONS

- Lumens: high spotlight-115, low spotlight-65
- Run-time: high spotlight-4.5 hrs, low spotlight-13 hrs
- Beam distance: 92 meters
- Water rating: IP-X7
- Drop rating: 2 meters
- Width: 2.4in, height: 1.9in, depth: 1.8in, weight: 3.5oz



Model	UPC 0 17398
XPP-5450G	80300 7
XPP-5452G	80301 4

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the lifetime of the original owner. Includes the LEDs, housing, lenses, electronics and switches. Batteries, normal wear and abuse are excluded.

Bayco Products, Inc. - 640 S. Sanden Blvd. - Wylie, TX 75098 - 800-233-2155 - baycoproducts.com