

3 AAA (included)

XPP-5452G

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

**NIGHTSTICK**<sup>®</sup>  
Life Depends on Light<sup>™</sup>



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



**Single Body Switch.** High-brightness Spotlight, Low-brightness Spotlight



**ANSI IP-67 Dustproof / Waterproof** with a 2 meter drop rating.



**Adjustable ratchet tilt head** made from an engineered polymer housing

CERTIFIED



**180 LUMENS**

1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

## INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

## 3 AAA INCLUDED

**ITEM NUMBER/UPC**

- XPP-5452G, UPC 0 1739880301 4

**MARKET APPLICATIONS**

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

**CERTIFICATIONS**

- cETLus, CE, ATEX, IECEx

**CASE MATERIAL**

- Engineered Polymer

**SPOTLIGHT LUMENS/RUNTIME**

- HIGH: 180L, 6 hrs. runtime  
- LOW: 90L, 19 hrs. runtime

**CANDELA**

- HIGH: 2,180  
- LOW: 962

**BEAM DISTANCE**

- HIGH: 93m  
- LOW: 62m

**DUST/WATER RATING**

ANSI IP-67 Dustproof / Waterproof

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 2.4 in (61 mm)  
- WIDTH: 1.9 in (48 mm)  
- DEPTH: 1.8 in (46 mm)  
- WEIGHT: 3.5 oz (1.6 Kg)

**BATTERY**







- 3 AAA (Included)

**WARRANTY**

- Limited lifetime warranty

**WHAT'S INCLUDED**

- Headlamp  
- 3 AAA batteries  
- Elastic non-slip headband  
- Rubber hardhat strap  
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	180 LUMENS	90 LUMENS
	6h	19h
	93m	62m
	2180cd	962cd
	2m	
	1m	

Bayco Products, Inc. XPP-5452G  
640 S. Sanden Blvd.  
Wylie, TX 75098



ID 4003544  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

Intertek

CLASS I DIV 1 GRPS A-D T3 Ex ia op is IIC T3 Ga  
CLASS II & III GRPS E-G T135C Intertek ITS 13 ATEX27854X  
CLASS I ZONE 0 AEx ia IIC T3 Ga IECEx ITS 17.0002X  
CLASS I ZONE 0 Ex ia IIC T3 Ga -20°C ≤ Tamb ≤ +40°C  
© II 1 G Ex ia op is IIC T3 Ga 1.5V/Cell AAA Alkaline

CE 2575

CERTIFIED

