

3 AA BATTERIES

XPP-5458G

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

NIGHTSTICK[®]
Life Depends on Light[™]



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



Adjustable ratchet tilt head made from an engineered polymer housing



Balanced weight distribution, reduces neck fatigue.

CERTIFIED



190 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

3 AA BATTERIES

ITEM NUMBER/UPC

- XPP-5458G, UPC 0 17398 80158 4

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, MSHA, UKCA

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- WHITE: 130L, 14 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH WHITE: 100L, 12 hrs. runtime
 - LOW WHITE: 25L, 70 hrs. runtime
 - GREEN: 21L, 37 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- 190L, 6 hrs. runtime

CANDELA

- 3,500

BEAM DISTANCE

- 120m

DUST/WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 3.3 in (843 mm)
 - WIDTH: 3.3 in (84 mm)
 - DEPTH: 3.5 in (89 mm)
 - WEIGHT: 9.5 oz (269 g)

BATTERY







- AA

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp
 - Elastic non-slip headband
 - Rubber hardhat strap
 - 3 AA batteries

FL 1 STANDARD	SPOT HIGH	FLOOD LOW	DUAL-LIGHT
	130 LUMENS	21 LUMENS	190 LUMENS
	14h	37h	6h
	120m		
	3500cd		
	2m		
	1m		

Permissible Nightstick XPP-5458G Headlamp
 APPROVAL No. 20-A130002-0

MSHA TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only.
 2) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only.
 3) Replace the batteries in fresh air only.
 4) Replace all batteries at the same time.
 5) Do not mix batteries from different manufacturers or of different types.
 6) The Model XPP-5458G Safety Headlamp must not be opened in areas where permissibility is required.
 7) The Model XPP-5458G Safety Headlamp is approved as a mine light under 30CFR, Part 20. It is not approve as a cap lamp under 30CFR, Part 19.

Intertek
 ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3 Ex ia I Ma
 CLASS II & III DIV 1 GRPS E-G T135C Ex ia IIC T3 Ga
 CLASS I ZONE 0 Ex ia IIC T3 Ga Intertek ITS 13 ATEX27838X
 CLASS I ZONE 0 Ex ia IIC T3 Ga IECEx ETL 13.0025X
 6 I M 1 Ex ia I Ma -20°C ≤ Tamb ≤ +40°C
 SECURITE INTRINSEQUE 6 I I G Ex ia IIC T3 Ga 1.5V/Cell AA Alkaline

UK CA

Conforms to:
 ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11, ANSI/ISA 60079-26

Certified to:
 CAN/CSA STD C22.2 No 157, CAN/CSA STD C22.2 No 60079-0, CAN/CSA STD C22.2 No 60079-11, CSA STD C22.2 No 25



© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPP-5458G-21

