

LI-ION RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT™ LANTERN

XPR-5586GX

NIGHTSTICK®

Life Depends on Light™

900

DUAL-LIGHT™ LUMENS



90° DOWNWARD ROTATION



Bottom-facing flood provides 650 lumens of soft unfocused light



Rear red safety lights provide visibility for machinery operators and driver safety.



Convenient locking snap-in charger included



Carry strap with seat belt style buckle for additional hands-free use



900 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

DUAL-LIGHT™ LANTERN

LI-ION RECHARGEABLE

ITEM NUMBER/UPC

XPR-5586GX, UPC# 017398807036

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- cULus, CE, BIS, UKCA, Meets requirements of NFPA-1971-8.6 (2013), Charger meets the requirements of NFPA-1901-14.1.10.2 (2016)

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 650L, 10 hrs. runtime
- MEDIUM: 380, 16 hrs. runtime
- LOW: 25L, 150 hrs. runtime

FLOODLIGHT

- HIGH: 650L, 10 hrs. runtime
- MEDIUM: 380, 16 hrs. runtime
- LOW: 25L, 150 hrs. runtime

DUAL-LIGHT

- HIGH: 900L, 8 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 37,600
- MEDIUM: 24,400
- LOW: 1,696

BEAM DISTANCE

FLASHLIGHT

- HIGH: 388m
- MEDIUM: 312m
- LOW: 83m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 10.25 in / 26 cm
- WIDTH: 4.25 in / 10.8 cm
- DEPTH: 5.5 in / 14 cm
- WEIGHT: 2 lbs. 13.3 oz. / 1283 g

BATTERY

- Rechargeable Li-ion battery pack

WARRANTY







- Limited lifetime warranty

PATENTED

- US PATENT 10,879,519

WHAT'S INCLUDED

- Lantern
- Li-ion rechargeable battery pack
- Locking snap-in charger (5586-CHGR1)
- AC & DC power supply
- Removable shoulder strap
- Instruction manual

FL 1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	650 LUMENS	650 LUMENS	900 LUMENS
	10h	10h	8h
	388m		
	37600cd		
	2m		
	1m		

Bayco Products, Inc. XPR-5586

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
UL listed for use with Bayco Li-ion Battery Pack 5586-BATT



E 467756
ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV1 GRPS E-G T135°C
CLASS I ZONE 0 GROUP IIC
-10°C ≤ Tamb ≤ +40°C
3.7V/Cell Li-ion



SEE INSTRUCTION MANUAL
VOIR MANUEL

MFG MM-YY

US Patent Pending

Meets the requirements of NFPA 1971-8.6 (2013)

CERTIFIED

