

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx UL 19.0013 Page 1 of 3 <u>Certificate history:</u>

Status: Current Issue No: 0

Date of Issue: 2020-02-27

Applicant: Bayco Products, Inc.

640S. Sanden Blvd. Wylie, Texas 75098 **United States of America**

Equipment: Floodlight, Nightstick XPR-5592**; optionally followed by GX

Optional accessory:

Type of Protection: Intrinsic Safety "ia", Optical Radiation "op is"

Marking: Ex ia op is IIC T4 Ga

-20°C ≤ Tamb ≤ +40°C

Approved for issue on behalf of the IECEx

Certification Body:

Katy A. Holdredge

Senior Staff Engineer

Position:

Date:

Signature:

(for printed version)

Kety a. Halbridge

2020-02-27

L. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

UL LLC 333 Pfingsten Road Northbrook IL 60062-2096 United States of America





IECEx Certificate of Conformity

Certificate No.: **IECEX UL 19.0013** Page 2 of 3

Date of issue: 2020-02-27 Issue No: 0

Manufacturer: Bayco Products, Inc.

640S. Sanden Blvd. Wylie, Texas 75098 **United States of America**

Additional manufacturing locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2011 Explosive atmospheres - Part 0: General requirements

Edition:6.0

Edition:6.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

IEC 60079-28:2015 Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation

Edition:2

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

US/UL/ExTR19.0015/00

Quality Assessment Report:

GB/ITS/QAR13.0005/05



IECEx Certificate of Conformity

Certificate No.: IECEx UL 19.0013 Page 3 of 3

Date of issue: 2020-02-27 Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The Model Nightstick XPR-5592 is a portable floodlight, containing 5 LEDs which is powered by a Bayco Li-ion Battery Pack Part No. BATT-5592. The device is provided with a black enclosure, clear polycarbonate lens, a metal frame with magnet, and an extendable handle to change the angle of the floodlight. To power on the device there is a SPDT switch that has a black rubber boot covering it.

Please see Annex for additional information.

SPECIFIC CONDITIONS OF USE: NO

Annex:

Annex to IECEx UL 19.0013 Issue 0.pdf



IECEx Certificate of Conformity

Certificate No.:

IECEx UL 19.0013

Issue No.: 0 Page 1 of 1

PARAMETERS RELATING TO THE SAFETY

Charging Voltage = 10 V

Only power the device with one Bayco part number 5592-BATT battery pack.

MARKING

Marking has to be readable and indelible; it has to include the following indications:



Bayco Products, Inc. XPR-5592 640 S. Sanden Blvd., Wylie, TX 75098


FLOODLIGHT FOR USE IN HAZARDOUS LOCATIONS
For use with Bayco Li-ion Battery Pack 5592-BATT only

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV1 GRPS E-G T135°C
CLASS I ZONE 0 GROUP IIC T4 Ga

II 1G Ex ia op is IIC T4 Ga
Ex ia op is IIC T4 Ga
DEMKO 19ATEX 2169

IECEx UL 19.0013 -20°C ≤ Tamb ≤ +40°C 5592-BATT 3.7V/Cell Li-ion Um 10V

WARNING: Do not charge battery in a hazardous location WARNING: Do not replace battery when an explosive atmosphere is present



MFG MM-YY