

MT-230

Mini-TAC Pro EMT

MARKET APPLICATIONS

Emergency medical technicians, fire & rescue, law enforcement

DESCRIPTION

This non-rechargeable Mini-TAC Pro light uses a CREE® LED and has a deep parabolic reflector creating a tight, long throw beam for distance illumination. With a waterproof design, it is constructed from aircraft-grade 6061-T6 aluminum with a Type III hard anodized finish. Because this light is designed for the special requirements of an EMT, the tail switch provides momentary or constant-on functionality and a set of user-selectable brightness modes that starts off in low-brightness mode and cycles up through the medium and high settings. The light come with a removable pocket clip and is powered by one included AA battery. Meets requirements of NFPA-1971-8.6 (2013).

CASE MATERIAL Aircraft-grade 6061-T6 Aluminum with a Type III Hard Anodized Finish - Blue

DIMENSIONS Length: 4 inches (102 mm) • Handle diameter: 0.6 inches (15 mm) • Head diameter: 0.9 inches (23 mm)

WEIGHT Weight: 2.2 oz. (62 g) with battery installed.

LIGHT SOURCE

Unbreakable polycarbonate with scratch resistant coating.

Cree® LED. Impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT

Low - 3.6 lumens, Medium - 10 lumens, High - 60 lumens

0N/0FF Single Tail Cap Switch - Momentary or Constant-on Flashlight, Low, Medium and High-Brightness Flashlight

RUN-TIME Low - 36 hours, Medium -14 hours, High - 2 hours

BATTERY 1 AA Premium Battery (included)

• Designed specifically for EMT usage

• CREE® LED technology - 50,000+ hours LED

• Momentary or constant-on, plus 3 user-selectable brightness settings plus strobe

Sharp focused flashlight beam

Aircraft-grade 6061-T6 aluminum housing

Type III hard anodized finish

Non-slip gripWaterproof

• waterproof

Impact & chemical resistant

Meets requirements of NFPA-1971-8.6 (2013)

Powered by 1 AA battery (included)

WARRANTY APPROVALS Limited Lifetime Warranty



FL1 STANDARD	LOW	MEDIUM	HIGH
314	3.6 LUMENS	10 lumens	60 LUMENS
0	36h	14h	2h
	4m	46m	65m
	4cd	538cd	1076cd
2m <i>■</i>		_	

