

NSR-9514B

Polymer Multi-Function Duty / Personal-Size Flashlight Rechargeable






MARKET APPLICATIONS	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
DESCRIPTION	The NSR-9514B rechargeable glass-filled nylon polymer LED flashlight, offers 3 microprocessor-controlled brightness modes as well as a strobe function. Utilizing a CREE® LED, the 9514B has an impressive runtime of 4.25 hours in full-brightness mode. The 350 lumen output in combination with the high efficiency deep parabolic reflector design throws a usable beam of light 313 meters...that's over 1,026 feet. The 9514B has a two button design, a switch located on the waterproof body of the light and one in the tail cap. Both switches operate in tandem with one another. Meets requirements of NFPA-1971-8.6 (2013).
CASE MATERIAL	Glass-filled Nylon Polymer w/ Aircraft-grade 6061-T6 Aluminum Tail Cap & Bezel both with a Type III Hard Anodized Finish - Black
DIMENSIONS	Length: 8.9 inches (226 mm) • Handle diameter 1.2 inches (30 mm) • Head diameter 1.6 inches (41 mm)
WEIGHT	Weight: 10.1 oz. (286 g) with battery installed.
LENS	Unbreakable polycarbonate with scratch resistant coating.
LIGHT SOURCE	Cree® LED. Impervious to shock with a 50,000 + hour lifetime.
LIGHT OUTPUT	High-Brightness - 350 lumens • Medium-Brightness - 200 lumens • Low-Brightness 55 lumens • Strobe - 300 lumens
ON/OFF	Single Body Switch & Single Tail Switch (Tandom Functionality) - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe
RUN-TIME	High-brightness - 4.25 hours • Medium-brightness - 8.5 hours • Low-brightness - 32.5 hours • Strobe - 5.5 hours
BATTERY	2-cell, 3.7 Volt Lithium-ion battery pack.
CHARGING	Charging platform is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.
FEATURES	<ul style="list-style-type: none"> • CREE® LED technology – 50,000 + hours LED life • Momentary or constant-on plus 3 brightness levels & strobe • Sharp focused beam • Glass-filled nylon polymer housing • Aircraft-grade 6061-T6 aluminum tail-cap and bezel both with a Type III hard anodized finish • Non-slip grip • Body & tail switch • Waterproof • Impact & chemical resistant • Meets requirements of NFPA-1971-8.6 (2013) • Serialized for personal identification • Powered by rechargeable Lithium-ion battery (included) • Includes wall or vehicle mounted charger as well as AC and DC power supply and anti-roll ring
WARRANTY	Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

APPROVALS



OPTIONAL ACCESSORIES

5 Bank Charger, Direct Wire Kit, USB Charging Cable, Red, Yellow & Blue Safety Cones

FL1 STANDARD	HIGH	MEDIUM	LOW
	350 LUMENS	200 LUMENS	55 LUMENS
	4h 15min	8h 30min	32h 30min
	313m	235m	118m
	24100cd	12075cd	6200cd
	2m		1m

