

# NIGHT STICK®

## Intrinsically Safe Polymer Penlight

*This penlight is cETLus, ATEX and IECEx listed Intrinsically Safe. It is ultra-compact and super slim with a powerful light output designed to illuminate very tight spaces. The tail-cap switch provides momentary or constant-on functionality. Power comes from 3 AAAA premium batteries (included).*

**INTRINSICALLY SAFE**



**50** Lumens

- cETLus, ATEX and IECEx listed Intrinsically Safe
- Engineered polymer housing
- Powered by AAAA batteries



**XPP 5412G**





# Intrinsically Safe Polymer Penlight

## XPP 5412G




XPP-5412G

### FEATURES

- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Engineered polymer housing
- Single tail switch
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Powered by 3 AAAA batteries (included)
- Limited Lifetime Warranty\*

### XPP-5412G SPECIFICATIONS

- Lumens: 50
- Run-time: 13.75 hrs
- Beam distance: 50 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 6.8in, head diameter: 0.6in, handle diameter: 0.5in, weight: 1.5oz



### INCLUDED

- Flashlight
- 3 AAAA premium alkaline batteries

### SAFETY RATING

cETLus, ATEX and IECEx listed Intrinsically Safe.

Patent 7,738,229

Model	UPC 0 17398
XPP-5412G	80299 4



Handheld

High-efficiency deep parabolic reflector

Push-button tail-cap switch

Nightstick 5412 Penlight

ID 4001184  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

Intertek

CLASS I DIV 1 GRPS A-D T3 Ex ia op is I Ma  
CLASS II & III DIV1 GRPS E-G T135C Ex ia op is IIC T3 Ga  
CLASS I ZONE 0 AEx ia IIC T3 Ga Intertek ITS 13 ATEX27839X  
CLASS I ZONE 0 Ex ia IIC T3 Ga IECEx ITS 14.0036X  
© I M 1 Ex ia op is I Ma -20°C ≤ Tamb ≤ +40°C  
© II 1 G Ex ia op is IIC T3 Ga 1.5V/Cell AAAA Alkaline  
C 0359

**Conforms to:** ANSIIUL STD 913, ANSIIUL 60079-0, ANSIIUL 60079-11, ANSIIISA 60079-26

**Certified to:** CAN/CSA STD C22.2 No 157, CAN/CSA STD C22.2 No 60079-0, CAN/CSA STD C22.2 No 60079-11, CSA STD C22.2 No 25

\*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.