

Intrinsically Safe Dual-Light™ Angle Light Rechargeable

Flashlight High Flashlight Medium Flashlight Low Flashlight Strobe



Floodlight High Floodlight Medium Floodlight Survival Dual-Light



TECHNOLOGY

200 Flashlight
Lumens

200 Floodlight
Lumens

200 Dual-Light™
Lumens



- cULus, MSHA, ATEX, and IECEx certified Intrinsically Safe
- Flashlight/Floodlight/Dual-Light™
- User-selectable brightness settings on Flashlight & Floodlight including 20 Lumen Survival mode on Floodlight
- Meets the requirements for NFPA-1971-8.6 (2013)
- Charger meets requirements of NFPA-1901 (2009)

The XPR-5572GA Rechargeable Intrinsically Safe Multi-Function Dual-Light™ Angle Light is a Flashlight, a Floodlight and a Dual-Light Angle Light that is cULus, MSHA, ATEX, and IECEx certified Intrinsically Safe. The flashlight setting offers 3 user-selectable brightness settings of 200, 100 and 60 Lumens plus a strobe feature with a 267 meter beam distance. The ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has 3 user-selectable brightness settings of 200, 100 and a "Survival Mode" of 20 lumens that provides just enough light in an emergency situation with a run-time of 3 ½ days. The Dual-Light mode allows the user to simultaneously see objects at a distance or through the smoke, as well as see the ground in front of them as they walk or work. The 5572 is powered by a rechargeable Lithium-ion battery pack. The 5572 meets requirements of NFPA-1971-8.6 (2013).

INTRINSICALLY SAFE



XPR 5572GA



SPECIFICATIONS