

# NIGHTSTICK®

## Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light Rechargeable

Flashlight High    Flashlight Medium    Flashlight Low    Flashlight Strobe



Floodlight High    Floodlight Medium    Floodlight Survival    Dual-Light



TECHNOLOGY

**200** Flashlight Lumens

**200** Floodlight Lumens

**200** Dual-Light™ Lumens



- cULus and MSHA certified Intrinsically Safe Permissible
- Flashlight/Floodlight/Dual-Light™
- User-selectable brightness settings on Flashlight & Floodlight including 20 Lumen Survival mode on Floodlight
- Meets the requirements for NFPA-1971-8.6 (2013)
- Charger meets requirements of NFPA-1901 (2009) mounted in any position

The XPR-5572R Rechargeable Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light is a Flashlight, a Floodlight and a Dual-Light Angle Light that is cULus and MSHA certified Intrinsically Safe Permissible. The flashlight setting offers 3 user-selectable brightness settings of 200, 100 and 60 Lumens plus a strobe feature with a 267 meter beam distance. The ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has 3 user-selectable brightness settings of 200, 100 and a "Survival Mode" of 20 lumens that provides just enough light in an emergency situation with a run-time of 3 ½ days. The Dual-Light mode allows the user to simultaneously see objects at a distance or through the smoke, as well as see the ground in front of them as they walk or work. The 5572 is powered by a rechargeable Lithium-ion battery pack. The 5572 meets requirements of NFPA-1971-8.6 (2013).

**INTRINSICALLY SAFE  
PERMISSIBLE**



**XPR 5572R**

# Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light Rechargeable



### FEATURES

- cULus and MSHA certified Intrinsically Safe Permissible
- CREE® LED technology – 50,000 + hours LED life
- Flashlight/Floodlight/Dual-Light™
- 3 User-selectable brightness settings on the flashlight plus a strobe
- High-efficiency deep parabolic reflector creating a sharp focused flashlight beam
- 3 User-selectable brightness setting on the floodlight including a 20 Lumen Survival Mode
- Dual-light (both the flashlight & floodlight on at the same time) provides for maximum lighting versatility and user safety
- Glass-filled Nylon Polymer housing
- Dual body switches
- Heavy-duty stainless-steel pocket clip
- Battery charge status indicator (for use only with rechargeable battery)
- Waterproof
- Impact & chemical resistant
- Light meets the requirements of NFPA-1971-8.6 (2013)
- Charger meets the requirements of NFPA-1901 (2009) mounted in any position
- Serialized for personal identification
- Powered by rechargeable Lithium-ion battery pack (included)
- Can also be powered by 6 AA batteries (not included) using the AA Battery Carrier (included)
- Limited Lifetime Warranty\*

### SPECIFICATIONS

- Lumens: flashlight high-200, medium-100, low-60, floodlight high-200, medium 100, survival 20, Dual-Light-200
- Run-time: flashlight high-6 hrs, medium-11 hrs 30 min, low- 22 hrs 30 min, floodlight high-6 hrs, medium-11 hrs 30 min, survival-30 hrs, Dual-Light-6 hrs
- Recharge time: 6 hours
- Beam distance: 267 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 7.6in, width: 3.2in, depth: 3in, bezel diameter: 2.8 in, weight: 13.7oz

FL 1 STANDARD	DUAL-LIGHT	HIGH	MEDIUM	LOW
	200 LUMENS	200 LUMENS	100 LUMENS	60 LUMENS
	8h	6h	11h	22h
	235m	267m	199m	145m
	13836cd	22249cd	14828cd	7790cd
	2m			1m

### INCLUDED

- Light
- Rechargeable Lithium-ion Battery Pack
- Wall or Vehicle Mounted Charger
- AA Battery Carrier (AA batteries not included)
- AC & DC Power Supplies



High-efficiency deep parabolic reflector

Wide-beam floodlight

Heavy-duty stainless-steel pocket clip

Wall or Vehicle Mounted Charger

### SAFETY RATING

cULus and MSHA certified Intrinsically Safe Permissible

Permissible Nightstick XPP-5570 Flashlight/Floodlight  
**MSHA** APPROVAL No. 20-A150005-0  
 TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY  
 WARNINGS: Do not charge in hazardous location. MSHA approved for use with Bayco Li-ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or L91 batteries. Replace the Battery Pack in fresh air only. Do not mix batteries from different manufacturers or different types. Battery Pack to be replaced by a qualified technician only. The Model Nightstick 5570 must not be opened in areas where permissibility is required. Substitution of components may impair Intrinsic Safety.

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
**UL** LISTED  
 E 467756  
 CE 0359

UL listed for use with Bayco Li-ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or E91 batteries.  
 CLASS I DIV 1 GRPS A D T3  
 CLASS II & III DIV 1 GRPS E-G  
 CLASS I ZONE 0 Group IIC T3  
 CLASS II ZONE 20 Group IIIC T3  
 -20°C ≤ Tamb ≤ +70°C

Model	UPC 0 17398
XPR-5572R	80458 5

\*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.