

# NIGHTSTICK®

## Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light w/ Multi-Angle Magnetic Base - Rechargeable



TECHNOLOGY

**200** Flashlight Lumens

**200** Floodlight Lumens

**200** Dual-Light™ Lumens



- cULus and MSHA certified Intrinsically Safe Permissible
- Flashlight/Floodlight/Dual-Light™
- Includes Multi-Angle Magnetic Base
- User-selectable brightness settings on Flashlight & Floodlight including 20 Lumen Survival mode on Floodlight
- Meets the requirements for NFPA-1971-8.6 (2013)
- Charger meets requirements of NFPA-1901 (2009) mounted in any position

The XPR-5572RM Rechargeable Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light w/Multi-Angle Magnetic Base is a Flashlight, a Floodlight and a Dual-Light Angle Light that is cULus and MSHA certified Intrinsically Safe Permissible. The flashlight setting offers 3 user-selectable brightness settings of 200, 100 and 60 Lumens plus a strobe feature with a 267 meter beam distance. The ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has 3 user-selectable brightness settings of 200, 100 and a "Survival Mode" of 20 lumens that provides just enough light in an emergency situation with a run-time of 3 ½ days. The Dual-Light mode allows the user to simultaneously see objects at a distance or through the smoke, as well as see the ground in front of them as they walk or work. The included Multi-Angle Magnetic Base adds an additional level of functionality to the 5572RM. The light slides into the magnetic base and locks in place. The powerful Rare-earth Magnet with its rubber protective covering will attach to virtually any ferrous metal surface. The single point locking lever can then be used in conjunction with the gimbal head to place the light coming from the 5572RM exactly where it's needed. The 5572RM is powered by a rechargeable Lithium-ion battery pack. The 5572RM meets requirements of NFPA-1971-8.6 (2013).

**INTRINSICALLY SAFE  
PERMISSIBLE**



**XPR 5572RM**



# Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light w/ Multi-Angle Magnetic Base - Rechargeable

### FEATURES

- cULus and MSHA certified Intrinsically Safe Permissible
- CREE® LED technology – 50,000+ hours LED life
- Flashlight/Floodlight/Dual-Light™
- 3 User-selectable brightness settings on the Flashlight plus a strobe
- High-efficiency deep parabolic reflector creating a sharp focused flashlight beam
- 3 User-selectable brightness setting on the Floodlight including a 20 Lumen Survival Mode
- Dual-light (both the flashlight & floodlight on at the same time) provides for maximum lighting versatility and user safety
- Glass-filled Nylon Polymer housing
- Dual body switches
- Heavy-duty stainless-steel pocket clip
- Battery charge status indicator (for use only with rechargeable battery)
- Multi-Angle Magnetic Base w/ powerful Rare-earth Magnet and locking gimbal head
- Waterproof
- Impact & chemical resistant
- Light (w/o magnetic base) meets the requirements of NFPA-1971-8.6 (2013)
- Charger meets the requirements of NFPA-1901 (2009) mounted in any position
- Serialized for personal identification
- Powered by rechargeable Lithium-ion battery pack (included)
- Can also be powered by 6 AA batteries (not included) using the AA Battery Carrier (included)
- Limited Lifetime Warranty\*

### SPECIFICATIONS

- Lumens: flashlight high-200, medium-100, low-60, floodlight high-200, medium 100, survival 20, Dual-Light-200
- Run-time: flashlight high-6 hrs, medium-11 hrs 30 min, low- 22 hrs 30 min, floodlight high-6 hrs, medium-11 hrs 30 min, survival-30 hrs, Dual-Light-6 hrs
- Recharge time: 6 hours
- Beam distance: 267 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 7.6in, width: 3.2in, depth: 3in, bezel diameter: 2.8 in, weight: 24.9oz w/ magnetic base

FL 1 STANDARD	DUAL-LIGHT	HIGH	MEDIUM	LOW
	<b>200 LUMENS</b>	<b>200 LUMENS</b>	<b>100 LUMENS</b>	<b>60 LUMENS</b>
	<b>8h</b>	<b>6h</b>	<b>11h</b>	<b>22h</b>
	<b>235m</b>	<b>267m</b>	<b>199m</b>	<b>145m</b>
	<b>13836cd</b>	<b>22249cd</b>	<b>14828cd</b>	<b>7790cd</b>
	<b>2m</b>			
	<b>1m</b>			

### INCLUDED

- Light
- Multi-Angle Magnetic Base
- Rechargeable Lithium-ion Battery Pack
- Wall or Vehicle Mounted Charger
- AA Battery Carrier (AA batteries not included)
- AC & DC Power Supplies



High-efficiency deep parabolic reflector

Wide-beam floodlight

Heavy-duty stainless-steel pocket clip

Wall or Vehicle Mounted Charger

<b>Model</b>	<b>UPC 0 17398</b>
XPR-5572RM	80466 0

\*Limited Lifetime Warranty - Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

### SAFETY RATING

cULus and MSHA certified Intrinsically Safe Permissible



Multi-Angle Magnetic Base w/ powerful Rare-earth Magnet and locking gimbal head

Permissible Nightstick XPP-5570 Flashlight/Floodlight

**MSHA** APPROVAL No. 20-A150005-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: Do not charge in hazardous location. MSHA approved for use with Bayco Li-Ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or E91 batteries. Replace the Battery Pack in fresh air only. Do not mix batteries from different manufacturers or different types. Battery Pack to be replaced by a qualified technician only. The Model Nightstick 5570 must not be opened in areas where permissibility is required. Substitution of components may impair Intrinsic Safety.

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

UL listed for use with Bayco Li-Ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or E91 batteries.

CLASS I DIV I GRPS A-D T3  
CLASS II & III DIV I GRPS E-G  
CLASS I ZONE 0 Group IIC T3  
CLASS II ZONE 20 Group IIIC T3  
-20°C ≤ Tamb ≤ +70°C

**UL** LISTED E 467756  
**CE** 0359