

NIGHT STICK®

Life Depends on Light™

Duty/Personal-Size Flashlights

Rechargeable - Multi-Function

POLYMER
HOUSING

High



Medium



Low



Strobe



350 Lumens

- 4.25 Hours run-time
- Momentary or constant-on with 3 brightness levels & strobe
- Beam distance rated at 313 meters
- Glass-filled nylon polymer housing
- Powered by Lithium-ion rechargeable battery



These rechargeable polymer multi-function duty/personal-size flashlights use a CREE® LED rated at 350 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable beam rated at 313 meters. The body & tail-cap switches provide momentary or constant-on functionality, a set of user-selectable high, medium or low-brightness settings as well as a disorienting strobe. Power comes from a rechargeable Lithium-ion battery.



NSR-9514B



NSR-9514Y

NSR 9500 series



High-efficiency deep parabolic reflector

Duty/Personal-Size Flashlights

Rechargeable - Multi-Function



NSR-9514Y



NSR-9514B

FEATURES: ALL MODELS

- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on plus 3 brightness levels & strobe
- Sharp focused beam
- Glass-filled nylon polymer housing
- Aircraft-grade 6061-T6 aluminum tail-cap & 316 stainless steel bezel, both with type III hard anodized finish
- Non-slip grip
- Body & tail-switch
- Waterproof
- Impact & chemical resistant
- Meets the requirements of NFPA-1971-8.6 (2013)
- Serialized for personal identification
- Powered by rechargeable Lithium-ion battery (included)
- Limited Lifetime Warranty*



High-efficiency deep parabolic reflector



Body switch



Tail-cap switch

SPECIFICATIONS

- Lumens: high-350, medium-200, low-55, strobe-300
- Run-time: high-4.25 hrs, medium-8.5 hrs, low-32.5 hrs, strobe-5.5 hrs
- Recharge time: 4 hours (typical)
- Beam distance: 313 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 8.9in, head diameter: 1.6in, handle diameter: 1.2in, weight: 10.1oz

FL1 STANDARD	HIGH	MEDIUM	LOW
	350 LUMENS	200 LUMENS	55 LUMENS
	4h 15min	8h 30min	32h 30min
	313m	235m	118m
	24100cd	12075cd	6200cd
	2m		1m

INCLUDED

- Flashlight
- Rechargeable Lithium-ion battery
- Wall/vehicle mountable charger
- Anti-roll ring
- AC power supply
- 12 V DC power supply



MODELS / ACCESSORIES

Model	Description	UPC 0 17398
NSR-9514B	Rechargeable dual switch black polymer flashlight with wall/vehicle mountable charger, battery, AC and 12V DC charging cords and anti-roll ring	80304 5
NSR-9514BDC	Rechargeable dual switch black polymer flashlight with wall/vehicle mountable charger, battery, 12V DC charging cord and anti-roll ring	80307 6
NSR-9514BLB	Rechargeable dual switch black polymer flashlight with battery and anti-roll ring	80310 6
NSR-9514Y	Rechargeable dual switch yellow polymer flashlight with wall/vehicle mountable charger, battery, AC and 12V DC charging cords and anti-roll ring	80474 5
NSR-9514YDC	Rechargeable dual switch yellow polymer flashlight with wall/vehicle mountable charger, battery, 12V DC charging cord and anti-roll ring	80496 7
NSR-9514YLB	Rechargeable dual switch yellow polymer flashlight with battery and anti-roll ring	80497 4
9600-BATT	Replacement Lithium-ion battery	80222 2
9600-USB	USB cord – 27in	80227 7
9600-RCONE	Red cone	80226 0
9600-YCONE	Yellow cone	80228 4
9600-BCONE	Blue cone	80223 9
9600-CHGR5	5 bank charger	80225 3
9810-LH	Leather holster	98101 9
9914-DW	Direct wire kit	80044 0



Safety cones



Leather holster



Spare Lithium-ion rechargeable battery



Five bank charger



USB charging cable



Direct wire kit

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.