

NIGHTSTICK®

Life Depends on Light™

Duty/Personal-Size Flashlights

Rechargeable - Multi-Function



High



Medium



Low



Strobe



350 Flashlight

- 4.25 Hours run-time
- Momentary or constant-on with 3 brightness levels & strobe
- Beam distance rated at 313 meters
- Aircraft-grade 6061-T6 aluminum housing
- Powered by Lithium-ion rechargeable battery



These rechargeable metal multi-function duty/personal-size flashlights use a CREE® LED rated at 350 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable beam rated at 313 meters. The single body switch model (9612) and the body & tail-cap switch model (9614) each provides momentary or constant-on functionality, a set of user-selectable high, medium or low-brightness settings as well as a disorienting strobe. Power comes from a rechargeable Lithium-ion battery.



NSR-9614B

NSR-9612B

NSR 9600 series




NIGHTSTICK

Life Depends on Light™

NSR 9600 series

NSR-9612B

NSR-9614B



Duty/Personal-Size Flashlights

Rechargeable - Multi-Function

High-efficiency deep parabolic reflector

FEATURES: ALL MODELS

- CREE® LED technology - 50,000+ hours LED life
- Momentary or constant-on plus 3 brightness levels & strobe
- Sharp focused beam
- Aircraft-grade 6061-T6 aluminum housing and tail-cap & 316 stainless steel bezel
- Type III hard anodized finish
- Non-slip grip
- Body & tail-switch (9614B) – body switch only (9612B)
- Waterproof
- Impact & chemical resistant
- Meets the requirements of NFPA-1971-8.6 (2013)
- Serialized for personal identification
- Powered by rechargeable Lithium-ion battery (included)
- Limited Lifetime Warranty*



High-efficiency deep parabolic reflector



Body switch (NSR-9612B/14B)



Tail-cap switch (NSR-9614B)

SPECIFICATIONS

- Lumens: high-350, medium-200, low-55, strobe-300
- Run-time: high-4.25 hrs, medium-8.5 hrs, low-32.5 hrs, strobe-5.5 hrs
- Recharge time: 4 hours (typical)
- Beam distance: 313 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 8.9in, head diameter: 1.6in, handle diameter: 1.2in, weight: 12.8oz

FLI STANDARD	HIGH	MEDIUM	LOW
	350 LUMENS	200 LUMENS	55 LUMENS
	4h 15min	8h 30min	32h 30min
	313m	235m	118m
	24100cd	12075cd	6200cd
	2m		1m

INCLUDED

- Flashlight
- Rechargeable Lithium-ion battery
- Wall/vehicle mountable charger
- Anti-roll ring
- AC power supply
- 12 V DC power supply



MODELS / ACCESSORIES

Model	Description	UPC 0 17398
NSR-9612B	Rechargeable single switch metal flashlight with wall/vehicle mountable charger, battery, AC and 12V DC charging cords and anti-roll ring/black	80216 1
NSR-9612BDC	Rechargeable single switch metal flashlight with wall/vehicle mountable charger, battery, 12V DC charging cord and anti-roll ring/black	80229 1
NSR-9612BLB	Rechargeable single switch metal flashlight with battery and anti-roll ring	80230 7
NSR-9614B	Rechargeable dual switch metal flashlight with wall/vehicle mountable charger, battery, AC and 12V DC charging cords and anti-roll ring/black	80217 8
NSR-9614BDC	Rechargeable dual switch metal flashlight with wall/vehicle mountable charger, battery, 12V DC charging cord and anti-roll ring/black	80231 4
NSR-9614BLB	Rechargeable dual switch metal flashlight with battery and anti-roll ring	80232 1
9600-BATT	Replacement Lithium-ion battery	80222 2
9600-USB	USB cord – 27in	80227 7
9600-RCONE	Red cone	80226 0
9600-YCONE	Yellow cone	80228 4
9600-BCONE	Blue cone	80223 9
9600-CHGR5	5 bank charger	80225 3
9810-LH	Leather holster	98101 9
9914-DW	Direct wire kit	80044 0



Safety cones



Leather holster



Spare Lithium-ion rechargeable battery



Five bank charger



USB charging cable



Direct wire kit

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.