

Intrinsically Safe Full-Size Polymer Dual-Light

This full-size rechargeable dual-light is cETLus listed intrinsically safe for use in Class I, Division I, Groups C, D & T4 hazardous workplace environments. This light uses 3 LEDs rated at a total of 240 lumens that work in conjunction with a tri-beam high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 175 meters. A 4 LED 155 lumens full-floodlight and a 2 LED 115 lumens half-floodlight is integrated into the housing which is perfect for close up illumination. Additionally both the flashlight and the half-floodlight can be turned on at the same time for maximum versatility. The dual body switches provide multiple lighting combinations including flashlight, full-floodlight, half-floodlight and dual-light operations. Power comes from a rechargeable Nickel Metal Hydride intrinisically safe battery.

INTRINSICALLY SAFE



240 Flashlight Lumens **155** Floodlight Lumens

- Class I, Div I, Groups C, D & T4
- Flashlight/full-floodlight/ half-floodlight/dual-light
- 175 Meter beam distance
- Engineered polymer housing



XPR-9864





Triple-beam flashlight







FEATURES

- cETLus listed intrinsically safe for use in Class I, Div 1, Groups C, D & T4 hazardous locations
- Flashlight full-floodlight half-floodlight dual-Light
- CREE® LED technology 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused flashlight beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-light (flashlight & floodlight at same time) for maximum versatility
- Engineered polymer housing
- Anti-roll tri-lobal head design
- Non-slip grip
- Dual body switches
- Water, impact & chemical resistant
- Serialized for personal identification
- Powered by rechargeable Nickel Metal Hydride intrinsically safe battery (included)
- Limited 2 Year Warranty**



Floodlight Dual-Light









Body switch



Shown with impact bumpers

SPECIFICATIONS

- Lumens: flashlight-240, full-floodlight-155, half-floodlight-115, dual-light-220
- Run-time: flashlight-9 hrs, full-floodlight-9.75 hrs, half-floodlight-13.25 hrs, dual-light-6.25 hrs
- Recharge time: 6 hours
- Beam distance: 175 meters
- Water rating: IP-X4 water resistant
- Drop rating: 2 meters
- Length: 13.6in, head diameter: 2in, handle diameter: 1.7in, weight: 27oz



INCLUDED

- Flashlight
- Rechargeable Nickel Metal Hydride intrinsically safe battery
- Wall/vehicle mountable charger
- AC power supply
- 12 V DC power supply
- Impact bumpers



ACCESSORIES

| Model | Description | UPC 0 17398 |
|--------------|---|----------------|
| XPR-9864 | Flashlight | 80263 5 |
| 9850-RCONE | Red safety cone | 98506 2 |
| 9850-YCONE | Yellow safety cone | 98505 5 |
| XPR-9862BATT | Intrinsically safe replacement NiMH battery | 80089 1 |
| 9862-BUMPERS | Impact bumpers | 80137 9 |
| 9850-BLAN | Elastic lanyard | 98507 9 |
| 9850-HOOK | Hanger hook | 98509 3 |
| 9850-WLAN | Wrist lanyard | 98508 6 |
| 9850-BRBW | Basket weave leather belt ring | 98501 7 |
| 9850-BRN | Nylon belt ring | 98502 4 |
| 9850-BRPL | Patent leather belt ring | 98503 1 |
| 9850-BRSL | Standard leather belt ring | 98504 8 |
| 9914-DW | Direct wire kit | 80044 0 |





batterv

lanyard





hook

Hanger Wrist

Elastic

bumpers



lanyard rings

^{*}Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the lifetime of the original owner. Includes the LEDs, housing, lenses, electronics and switches. Rechargeable batteries and chargers are warranted for a period of one year. Excludes normal wear and abuse.