

3 AAA (included)

XPP-5450G

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

**NIGHTSTICK**  
Life Depends on Light™



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



**Single Body Switch.** High-brightness Spotlight, Low-brightness Spotlight



**ANSI IP-67 Dustproof / Waterproof** with a 2 meter drop rating.



ATEX  
**ZONE 0**  
IECEx

**CLASS I  
DIV 1**

IP-X7  
**WATER  
PROOF**



**Adjustable ratchet tilt head** made from an engineered polymer housing



**90 LUMENS**

1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

© 2024 BPI Items shown are intended as a visual representation only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

# INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

## 3 AAA INCLUDED

### ITEM NUMBER/UPC

- XPP-5450G, UPC 0 1739880300 7

### MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

### CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, Kosha, INMETRO

### CASE MATERIAL

- Engineered Polymer

### SPOTLIGHT LUMENS/RUNTIME

- HIGH: 90L, 13.5 hrs. runtime  
- LOW: 50L, 22.75 hrs. runtime

### CANDELA

- HIGH: 1,615  
- LOW: 1,076

### BEAM DISTANCE

- HIGH: 80m  
- LOW: 65m

### DUST/WATER RATING

ANSI IP-67 Dustproof / Waterproof

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 2.4 in (61 mm)  
- WIDTH: 1.9 in (48 mm)  
- DEPTH: 1.8 in (46 mm)  
- WEIGHT: 3.5 oz (99 g)

### BATTERY







- 3 AAA (Included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Headlamp  
- 3 AAA batteries  
- Elastic non-slip headband  
- Rubber hardhat strap  
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	90 LUMENS	50 LUMENS
	13h	22h
	80m	65m
	1615cd	1076cd
		
		

Bayco Products, Inc. XPP-5450G  
640 S. Sanden Blvd.  
Wylie, TX 75098



Intertek  
ID 4003544

INTRINSICALLY SAFE  
SECURITE INTRINSEQUE



2575



0359



22-AVABO-0216X



CLASS I DIV 1 GRPS A-D T4  
CLASS II & III GRPS E-G T135C  
CLASS I ZONE 0 AEx ia IIC T4 Ga  
CLASS I ZONE 0 Ex ia IIC T4 Ga  
© II 1 G Ex ia op is IIC T4 Ga

Ex ia op is IIC T4 Ga  
Intertek ITS 13 ATEX27854X  
ITS21UKEX0247X  
IECEx ITS 17.0002X  
-20°C ≤ Tamb ≤ +40°C  
1.5V/Cell AAA Alkaline

#### CERTIFIED

