

LI-ION RECHARGEABLE

DICATA™ INTRINSICALLY SAFE DUAL-LIGHT USB HEADLAMP

XPR-5562GX

NIGHTSTICK®

Life Depends on Light™



MAGMATE™ Magnetic Coupler
USB Rechargeable.



Enlarged front-mounted dual switches, easily toggle through the beam options with gloves on.



Low Profile for Visor Clearance, on most helmets & hard hats.



Dual-Light Technology, focused spotlight and area floodlight at the same time.



**CLASS I
DIV 1**

**DUAL
LIGHT®
TECHNOLOGY**

**IP-67
DUST/WATER
PROOF**

300 LUMENS

CERTIFIED



1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

LI-ION BATTERY

ITEM NUMBER/UPC

- XPR-5562GX, UPC 0 17398 80774 6

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS

- cULus, ATEX, IECEX, CE, NFPA

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 275L, 6 hrs. runtime

- LOW: 100L, 15 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH: 250L, 6 hrs. runtime

- LOW: 100L, 15 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- 300L, 5 hrs. runtime

CANDELA

- HIGH: 3,660

BEAM DISTANCE

- 120 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 1.25 in (31 mm)

- WIDTH: 3.75 in (95 mm)

- DEPTH: 1 in (25 mm)

- WEIGHT: 5.8 oz (164 g) without battery

POWER SOURCE

- Integrated Li-ion

WARRANTY

- Limited lifetime

WHAT'S INCLUDED







- Headlamp

- Li-ion Battery

- Heavy-duty rubber head strap

- 4' (304 mm) USB Male (Type A) Magnetic Coupler Charge Cord

- Instruction Manual

FL 1 STANDARD	SPOT HIGH	FLOOD HIGH	DUAL-LIGHT
	275 LUMENS	250 LUMENS	300 LUMENS
	6h	6h	5h
	120m		
	3660cd		
	2m		
	1m		



E 467756
ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE



WARNING: Do not charge battery in a hazardous location.

SEE INSTRUCTION MANUAL
VOIR MANUEL

Meets Requirements of NFPA-1971-8.6 (2013)

Bayco Products, Inc. XPR-5562GX

640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
UL listed for use with Bayco Li-ion Battery Pack 5562-BATT

CLASS I DIV 1 GRPS A-D T4

CLASS II & III DIV 1 GRPS E-G T135°C

CLASS I ZONE 0 AEx ia op is IIC T4 Ga

© II 1 G Ex ia op is IIC T4 Ga

Ex ia op is IIC T4 Ga

DEMKO 20 ATEX 2267

IECEX UL 20 0036

-20°C ≤ Tamb ≤ +40°C

3.7V/Cell 5562-BATT

Um 4.2V

WARNING: Do not replace battery when an explosive atmosphere is present

MFG MM-YY

US Patent 9,713,217

CERTIFIED

