

RECHARGEABLE

INTRANT™ DUAL-LIGHT ANGLE LIGHT

**NIGHTSTICK®**  
Life Depends on Light™



HEAD ROTATES 90°

45°

EXCLUSIVE  
DOWNWARD FLOODLIGHT


GRAB-N-GO  
CHARGING BASE



**Head rotates 90°** – directing beam exactly where it's needed most



**45° downward floodlight** lights an 8 foot walking area



**Easy-to-use with gloves**, the large switches **independently control** separate LEDs



**Heavy-duty, clip and V-ring** securely holds **tight to gear** in any situation



ALSO AVAILABLE IN SAFETY RED.



**205 LUMENS**

1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

© 2023 Bayco Products Inc. Items shown are intended as a visual representation only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

# DUAL-LIGHT ANGLE LIGHT

## RECHARGEABLE

### ITEM NUMBER/UPC

XPR-5568RX (Red), 0 17398 80631 2  
 XPR-5568RLB (Red, Light & Battery Only), 0 17398 80697 8  
 XPR-5568GX (Green), 0 17398 80630 5

### CERTIFICATIONS

- CE, cULus, ATEX, IECEx, InMetro, UKCA  
 - Meets requirements of NFPA

### PATENTS

- 9,713,217 10,119,663

### CASE MATERIAL

- Engineered polymer

### LUMENS/RUNTIME

#### FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime  
 - MEDIUM: 110L, 15 hrs. runtime  
 - LOW: 60L, 27 hrs. runtime  
 - STROBE

#### FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime  
 - MEDIUM: 40L, 15 hrs. runtime  
 - SURVIVAL: 20L, 27 hrs. runtime

#### DUAL-LIGHT

- 205L, 7 hrs. runtime

### CANDELA

#### FLASHLIGHT

- HIGH: 40,256  
 - MEDIUM: 15,625  
 - LOW: 8,750

### BEAM DISTANCE

#### FLASHLIGHT

- HIGH: 401m  
 - MEDIUM: 250m  
 - LOW: 187m

### WATER RATING

- IP-67 (dustproof and waterproof)

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 6.6 in (168mm)  
 - WIDTH: 2.6 in (66mm)  
 - DEPTH: 2.6 in (66mm)  
 - HEAD DIAMETER: 2.1 in (53mm)  
 - WEIGHT: 10.6 oz (301g)(with batteries)

### BATTERY

- Rechargeable Li-ion battery pack  
 - AA Battery carrier (batteries not included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Angle light  
 - Rechargeable Li-ion battery pack  
 - AA battery carrier  
 - Snap-in rapid charger (Charge Input: 12VDC max) Meets requirements of NFPA  
 - AC & DC power supplies  
 - Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	7h	27h	7h
	401m		
	40256cd		



E-687795  
 ID 4003544

ELECTRICAL SAFETY  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE

CE 2575  
 UK CA 0359

Meets the requirements of  
 NFPA-1971-8.6 (2013)

DEMCO 17 ATEX 1927  
 UL2008K2420  
 IECEx UL 17.0882  
 20°C ≤ Tamb ≤ +40°C  
 1.5V/Cell Alkaline  
 3.7V/Cell Li-ion  
 P-67  
 Um: 10V

SEE INSTRUCTION MANUAL  
 VOIR MANUEL

US Patents 9,713,217 & 10,119,663

Control Drawing: 5568-CERT-DWG1-03  
 For Battery Charger Connection see Instruction  
 Manual Drawing: 5562-45-MECH-DWG1-09

MFG MM-YY

CERTIFIED

CE cULus LISTED

EX IECEx

NFPA UK CA 0359

InMetro BC

8